

Hybrid Solar Dispatcher



- Pure sine wave inverter
- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function
- Parallel operation with up to 6 units only available for 4KVA/5KVA
- Optional Remote Control Panel available

INVERTER/CHARGER

Hybrid solar Dispatcher Selection Guide

MODEL	HSD EF MPPT 1K-24	HSD EF MPPT 1K-48	HSD EF MPPT 2K-24	HSD EF MPPT 3K-24	HSD EF MPPT 3K-48	HSD EF MPPT 4K-48	HSD EF MPPT 5K-48
Rated Power	1000VA/800W	1000VA/1000W	2000VA/1600W	3000VA/2400W	3000VA/2400W	4000VA/3200W	5000VA/4000W
INPUT							
Voltage	120 VAC or 230 VAC			230 VAC			
Selectable Voltage Range	95-140 VAC or 170-280 VAC (For Personal Computers) 65-140 VAC or 90-280 VAC (For Home Appliances)			170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)			
Frequency Range	50 Hz/60 Hz (Auto sensing)						
OUTPUT							
AC Voltage Regulation (Batt. Mode)	110/120 VAC ± 5% (User selectable) or 230VAC ± 5%			230VAC ± 5%			
Surge Power	2000VA		4000VA	6000VA	8000VA	10000VA	
Efficiency (Peak)	90% - 93%			93%			
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)						
Waveform	Pure sine wave						
BATTERY & AC CHARGER							
Battery Voltage	24 VDC	48 VDC	24 VDC	24 VDC	48 VDC	48 VDC	
Floating Charge Voltage	27 VDC	54 VDC	27 VDC	27 VDC	54 VDC	54 VDC	
Overcharge Protection	31 VDC	62 VDC	31 VDC	31 VDC	62 VDC	60 VDC	
SOLAR CHARGER & AC CHARGER							
Maximum PV Array Power	600 W	900 W	600 W	600 W	900 W	3000 W	
MPPT Range @ Operating Voltage	30VDC ~ 66VDC	60VDC ~ 88VDC	30VDC ~ 66VDC	30VDC ~ 66VDC	60VDC ~ 88VDC	60VDC ~ 115VDC	
Maximum PV Array Open Circuit Voltage	75 VDC	102 VDC	75 VDC	75 VDC	102 VDC	145 VDC	
Maximum Solar Charge Current	25A	18 A	25A	25A	18 A	60 A	
Maximum AC Charge Current	10 A / 20 A	10 A / 15 A	20 A or 30 A	20 A or 30 A	10 A / 15 A	60 A	
Maximum Charge Current	25A	18 A	30A	30A	18 A	120A	
Maximum Efficiency	98%						
Standby Power Consumption	2 W						
PHYSICAL							
Dimension, D x W x H (mm)	100 x 272 x 355					140 x 295 x 540	
Net Weight (kgs)	6.8		7.0	7.4	12.5	13.5	
OPERATING ENVIRONMENT							
Humidity	5% to 95% Relative Humidity(Non-condensing)						
Operating Temperature	0°C - 55°C						
Storage Temperature	-15°C - 60°C						

* There are charging current selection only available for 230VAC system. Product specifications are subject to change without further notice

Energy Flow GmbH

Germany: 4 Friedrichstraße,
45128 Essen, NRW
Bulgaria: 12 Gen. Skobelev Str.,
6100 Kazanlak, Stara Zagora

GSMs: Martin Zhelev +359 885 74 44 50
Stoyan Zhelev +359 887 26 28 27
Volen Makedonski +359 899 10 99 69
Fax: +359 431 6 44 28
e-mail: energyflow.org@gmail.com
website: www.energy-flow.org
www.ef-panels.com